

Global Leader

NEA® Electronics, Inc. is a global leader in spacecraft mechanisms. Our low shock release devices are relied upon for spaceflight applications more than any other device.

Reliable

Our designs are reliable, simple, insensitive to adverse environments and backed up by years of heritage and loyal customers.

Quality Assured

NEA, a trusted supplier of mission critical components, is certified to ISO 9001:2008 and AS9100:2009 C

NEA Model DF Dead Face Connector

Model DF Product Data Sheet

NEA's Dead Face (DF) connectors are reliable in-flight electrical disconnects for satellite and spacecraft separation, missile staging, and umbilical separation. In addition to providing precision separation force, DF connectors provide electrical isolation prior to physical separation.

Applications

- Typical applications include:
- Satellite, spacecraft and payloads
- Stage separation
- Umbilical disconnects
- Panel disconnect assemblies
- Harsh environments

Principle of Operation

NEA's DF electrical interconnects incorporate standard MIL-DTL-38999 inserts and MIL-C-39029 pin and socket contacts. DF connectors have an internal shuttle that disconnects and isolates electrical signals prior to physical separation at the separation plane, assuring upstream integrity of electrical interfaces, even during harsh environmental conditions after separation.

DF connectors are designed to work in conjunction with NEA's ZSF100P connectors at the separation interface. Each mated connector pair is factory calibrated to compensate for connector pin engagement and other retention forces, assuring precise and smooth separation. DF connectors feature a floating shell, eliminating jamming during mating and separation. Blind engagement of the plug and receptacle pairs is possible, since the connectors allow for linear and angular misalignment. Connectors can be mounted from the rear of the panel or bracket, allowing for ease of installation. The back side of the DF connector mates with a MIL-C-38999 Series III plug.



Key Features

- Absolute electrical isolation prior to separation at the separation plane
- Zero, positive, or negative separation force
- Mounts from rear of panel or bracket
- Tolerates wide range of linear and angular misalignment permitting blind engagement
- MIL-DTL-38999 insert configurations
- Full range of keying configurations
- Service Class H
- Utilizes MIL-C-39029 pin and socket contacts
- Complete harness and disconnect assemblies available
- DF200 and 201 series mates with our Model ZSF100 connectors

NEA Model DF Dead Face Connector

Model DF Dead Face Connector Configurations

Connector Model	Style	MIL-DTL-38999		
		Shell Size ¹	Insert Arrangement ¹	Mates With
DF200SS	Receptacle	17	8	ZSF100P ²
DF200SS, 201SS	Receptacle	25	7, 29, 24, 61, 90	ZSF100P ²

Notes:

¹Existing shell sizes and insert arrangements shown. Other MIL-DTL-38999 shell size and insert arrangements available.

²See data sheet for NEA Model ZSF100 connectors

Model DF Technical Specifications

Parameter	Capability
Separation Force	0 N (0 lbf) (or adjustable to customer spec)
Engagement Force	90 N (20 lbf)
Linear Misalignment	0.76mm (0.03 in) min
Maximum Angular Misalignment	5° cone (half cone)
Qualification Temperature Range ¹	-55°C to +200°C at 10-4 Torr
Short Duration Firewall	1,343°C
Shock ²	14,200 G peak
Random Vibration ²	17 Grms, 180 sec per axis
Insulation Resistance	100MΩ min at 1500 VDC
Dielectric Withstanding Voltage	2mA max leakage at 1000 VAC
Shell to Shell Conductivity	10mV drop at 1A
Mass ³	380 g (0.84 lb)

Notes:

¹The values presented for qualification temperature range are not a measure of the limits of the device.

²Shock and random vibration testing performed in the mated and unmated configurations.

³Representative of DF200SS, 25-24 insert arrangement with electrical contacts. Contact NEA Electronics for other configurations.

Model DF Mechanical Interface

NEA Dead Face connector mechanical interfaces are compliant with MIL-DTL-38999.

NEA® Electronics, Inc., 14370 White Sage Road, Moorpark, California 93021, USA | neaelectronics.com

NEA® is a registered trademark of NEA Electronics, Inc. This product and its components are protected under U.S. Patent Numbers 6,433,990 / 6,249,063 as well as France Patent Numbers 125567 / 9903335, U.K. Patent Number 1255675 and Germany Patent Number 60111923.1.

Attention: The information and recommendations described in this brochure cannot possibly cover every application of the products or variation of conditions under which the products are used. The recommendations herein are based on the manufacturer's experience, research and testing. They are believed to be accurate, but no warranties are made, express or implied. In addition, the specifications contained herein are all nominal which represent our current production. The products described may be subject to change. Please feel free to contact NEA® Electronics Inc. for verification. No Warranties or Liabilities: The products described herein are sold "AS IS" and without any warranty or guaranty, express, or implied, arising by law or otherwise including without limitation any warranty of merchantability or fitness for a particular purpose. Buyer and user agree further to release and discharge seller from any and all liabilities whatsoever arising out of the purchase or use of any product described herein whether or not such liability is occasioned by seller's negligence or based upon strict products liability or upon principles of indemnity or contribution. Content©2014 NEA® Electronics, Inc., Moorpark, CA 93021, U.S.A.

Cleared for Open Publication by the Office of Security Review, Department of Defense 04/24/2014 14-S-1253

Mission Success

NEA® Electronics, Inc. is dedicated to building mankind's legacy in space by supporting our customers in the aerospace industry through on time delivery of innovative products that exceed expectations and assure mission success.

