

ACE® Sliding Charge

The ACE® Sliding Charge is a pre-made advanced breaching tool that incorporates ACE® Cutting Charges, SOB® Slip-On-Boosters, and Detonating Cord into a ready-made charge for explosive door breaching. Each section of ACE® has hydrogel tape for easy attachment to the target and the detonating cord slides inside the boosters allowing for flexibility in charge placement.

The charge assembly is vacuum-sealed in a barrier bag for maximum protection and storage life. The Pre-Made Charge is manufactured under controlled conditions, providing high consistency, quality, and reliability. All of the explosive components are designed, manufactured, and qualified for use by United States Military and International Forces.

APPLICATION:

- Designed to defeat hinges and locks on wood and metal doors
- No field assembly required – open and go
- Each charge section slides along the detonating cord allowing them to be individually positioned to meet target needs

PROPERTIES:

- ACE® - Three or four 10" (250 mm) lengths
- Detonating Cord - 50 gr/ft (10 g/m) - 12" (4.6 m) for attachment of standard military detonators
- SOB® Slip-On-Booster - for reliable initiation and detonation transfer
- Hydrogel - for target placement
- Compliant with Montreal Protocol taggant (tracer) levels



EX2016070449
Charges, Demolition, UN0048
1.1D

ACE® SLIDING CHARGE

PART** NUMBER	EXPLOSIVE MATERIAL	CHARGE SIZE (NOMINAL)		STEEL PLATE SEVERANCE (TYPICAL)		NET EXPLOSIVE WEIGHT (NOMINAL)*	
		grain/foot	gram/meter	in	mm	lb	gram
D12180-3-0300	RDX (charge) PETN (booster and cord)	300	63	0.20	5.1	0.27	120.8
D12180-4-0300						0.30	137.0
D12180-3-0450	RDX (charge) PETN (booster and cord)	450	100	0.28	7.1	0.32	145.1
D12180-4-0450						0.37	169.5
D12180-3-0600	RDX (charge) PETN (booster and cord)	600	125	0.36	9.1	0.37	169.5
D12180-4-0600						0.44	201.9
D12180-3-0900	RDX (charge) PETN (booster and cord)	900	190	0.44	11.1	0.48	218.18
D12180-4-0900						0.59	266.88

*Net Explosive Weight includes ACE® charges, Detonating Cord, and SOB® Slip-On-Boosters.

**A - 3 for three charges and - 4 for four charges

OPERATIONAL STEPS:

1. The ACE® Sliding Charge is deployed by removing the backing strips from the adhesive strips on each of the ACE® charges.
2. The charges are then placed on the specific target locations (typically the hinges and/or locks) and pressed in place.
3. Once the charge is deployed, the detonator from an EBAD SKIN-PACK® or equivalent initiation device is attached to the detonating cord using an accepted method of attachment.



ENSIGN-BICKFORD AEROSPACE & DEFENSE COMPANY
640 HOPMEADOW STREET, P.O. BOX 429, SIMSBURY, CT 06070, USA www.EBAD.com

SKIN-PACK®, PRIMASHEET®, DETASHEET®, ACE® and SOB® are registered trademarks of EBAD.

Attention: The information and recommendations described in this brochure cannot possibly cover every application of the products or variation of conditions under which the products are used. The recommendations herein are based on the manufacturer's experience, research and testing. They are believed to be accurate, but no warranties are made, express or implied. In addition, the specifications contained herein are all nominal which represent our current production. The products described may be subject to change. Please feel free to contact Ensign-Bickford Aerospace & Defense Company for verification. No Warranties or Liabilities: THE PRODUCTS DESCRIBED HEREIN are sold "AS IS" and without any warranty or guaranty, express, or implied, arising by law or otherwise including without limitation any warranty of merchantability or fitness for a particular purpose. Buyer and user agree further to release and discharge seller from any and all liabilities whatsoever arising out of the purchase or use of any product described herein whether or not such liability is occasioned by seller's negligence or based upon strict products liability or upon principles of indemnity or contribution. Content©2021 Ensign-Bickford Aerospace & Defense Company, Simsbury, CT 06070, U.S.A.